

SAFETY DATA SHEET

Nylar 100 (HSE No.: 6234)

Page 1 of 4 Revision No. 1

Issue date: 07 March 2005

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product name Nylar 100

Company PelGar International Ltd

Unit 13, Newman Lane Industrial Estate, Newman Lane, Alton, Hampshire

GU34 2QR

Telephone Tel +44 (0) 1420 80744

Telefax Fax +44 (0) 1420 80733

Product code 301

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components Pyriproxyfen 1-10% Iso-butanol 1-10%

CAS: 95737-68-1 CAS: 78-83-1 EINECS: 94-04-069500 EINECS: 201-148-0

N;R50/53 R10 Xi;R37 Xi;R38 Xi;R41 -;R67

C9 – C11 alcohol with 8 moles ethylene oxide 1-10%

CAS: 68439-45-2 Xn;R22 Xi;R41

Solvent Naphtha (petroleum), Heavy aromatic 70-80%

N;R51/53 Xn;R65

3. HAZARDS IDENTIFICATION

Most important hazardsToxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed.

Specific hazards Product can accumulate static charges, which can cause an incendiary electrical discharge.

Material can form flammable mixtures or can burn only if heated to temperatures at or above the

flash point.

4. FIRST AID MEASURES

Skin contact Remove contaminated clothing Wash off immediately with soap and plenty of water. If irritation

persists obtain medical attention. Contaminated clothing should be washed and dried before re-

use

Eye contact Rinse immediately with plenty of water for at least 15 minutes. If irritation persists obtain

medical attention

Inhalation Move to fresh air. Obtain medical advice immediately.

Ingestion Harmful: may cause lung damage if swallowed. Do not induce vomiting. If conscious give a

small amount of milk or water to drink and obtain medical attention. Show the container label or

this Safety Data Sheet to the doctor.

General advice In the case of accident or if you feel unwell, seek medical advice immediately (show the label

where possible).

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Keep fire exposed containers cool by spraying with water if exposed to fire. Fight surrounding

fire with foam, dry chemical, water spray or mist

Nylar 100

Page 2 of 4 Revision No. 1

Issue date: 07 March 2005

Extinguishing media which must not be used for safety reasons

Do not use water jets

Specific hazards Combustible material. Fire may cause toxic fumes (oxides of carbon) to evolve. Avoid spraying

water directly into storage containers due to danger of boil over.

Special protective

equipment for firefighters

In the event of fire, wear a self-contained breathing apparatus and a chemical protection suit,

gloves and boots.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Wear suitable protective clothing, gloves and eye/face protection. See section 8. Keep public

away. Remove all sources of ignition.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Contain or absorb leaking liquid with earth or sand. Prevent liquid entering watercourses, sewers or basements. Prevent product from entering drains. If substance has entered a watercourse or sewer or contaminated soil or vegetation,

inform the appropriate authority.

Methods for cleaning up Soak up with inert absorbent material. Transfer to a suitably labelled container. Subsequently,

wash the contaminated area with water, or detergent and water, taking care to prevent the washings from entering surface drains. For large spills, recover by pumping (use a hand pump or

explosion proof pump).

7. HANDLING AND STORAGE

Handling

Material will accumulate static charge, which may cause an electrical spark (ignition source). Take precautionary measures against static discharges. Do not apply in the presence of naked flames, hot surfaces or unprotected electrical equipment. Container remains hazardous when empty. Continue to observe all precautions. The product is flammable but not readily ignited. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Keep away from sources of ignition - No smoking. If splashing is likely to occur wear approved eye protection. If spray mists are likely, wear a suitable approved respirator. If skin contact is likely to occur wear rubber gloves and suitable impervious protective clothing. Use in a well ventilated area where possible. Always use good personal hygiene procedures when handling chemicals. Do not smoke eat or drink while handling this product. Wash hands, face and exposed skin after using, and before eating, drinking or smoking. Read the label before use. Keep product and empty container away from heat and sources of ignition.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep away from food and animal feedstuffs Store in accordance with Health and Safety Executive's Guidance Note HSG71 Keep away from oxidising agents. Keep away from sources of ignition.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limit(s) 2-Methylpropan-1-ol

TWA(ppm):50 TWA(mg/m3):154 STEL(ppm):75 STEL(mg/m3):231

Aromatic hydrocarbon

TWA(ppm):25 (for trimethyl benzene) TWA(mg/m3):125 for (trimethyl benzene)

Engineering measures The use of mechanical (explosion proof) dilution ventilation is recommended whenever this

product is used in a confined space.

Respiratory protection Suitable approved respirator if exposed to spray mists

Hand protection Rubber or plastic gloves

Eye protection If splashes are likely to occur, wear: goggles

Skin and body protection Impervious clothing boots

9. PHYSICAL AND CHEMICAL PROPERTIES

Description Liquid

Nylar 100

Page 3 of 4 Revision No. 1

Issue date: 07 March 2005

Colour Pale straw

Odour Characteristic

pH N/D

Boiling point/range No Data

Flash point 66°C

Relative density 0.91

Water solubility Miscible

10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

Conditions to avoid Heat, flames and sparks.

Materials to avoid Strong oxidising agents, strong bases

Hazardous decomposition

products

Oxides of carbon, smoke.

11. TOXICOLOGICAL INFORMATION

Acute toxicity Harmful: may cause lung damage if swallowed. ORL RAT LD50 >5000mg/Kg

DERMAL RAT LD50 >2000mg/Kg INH RAT LC50 1300mg/Kg (4hr exposure)

Primary irritation Irritating to eyes, respiratory system and skin.

Sensitisation No Data

Repeated or prolonged

exposure

Prolonged skin contact may defat the skin and produce dermatitis.

Mutagenic effectsNot availableCarcinogenic effectsNot availableReproductive toxicityNot available

12. ECOLOGICAL INFORMATION

Ecotoxicity effectsToxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

General Information Dispose of as special waste in compliance with local and national regulations.

Contaminated packaging Dispose of as unused product.

14. TRANSPORT INFORMATION

ADR/RID

UN-No 3082 Packing group III
Class 9 Hazard ID 90

Proper shipping name ENVIRONMENTALLY

HAZARDOUS SUBSTANCE,

LIQUID, N.O.S.

IMO

UN-No 3082 Packing group III
Class 9 Marine pollutant YES

EmS F-A S-F

IATA-DGR

Page 4 of 4 Revision No. 1

Issue date: 07 March 2005

UN-No 3082 Class 9 packaging 914 Packing group III Sub-risks -

15. REGULATORY INFORMATION

Symbol(s): Xn - Harmful; N - Dangerous for the environment

X_n¥zz

R-phrase(s) R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 - Harmful: may cause lung damage if swallowed.

R10 - Flammable.

R36/37/38 - Irritating to eyes, respiratory system and skin.

S-phrase(s)To avoid risks to man and the environment, comply with the instructions for use.

S25 - Avoid contact with the eyes.

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S28 - After contact with skin, wash immediately with plenty of soap and water

S29 - Do not empty into drains.

S37/39 - Wear suitable gloves and eye/face protection.

S60 - This material and its container must be disposed of as hazardous waste.

S61 - Avoid release to the environment. Refer to special instructions/safety data sheets.

S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

16. OTHER INFORMATION

Text of R phrases mentioned in Section 2

R10 - Flammable.

R22 – Harmful if swallowed.

R37 - Irritating to respiratory system.

R38 - Irritating to skin.

R41 - Risk of serious damage to eyes.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 - Harmful: may cause lung damage if swallowed.

R67 - Vapours may cause drowsiness and dizziness.

Recommended restrictions Insecticide for professional use only.

Further information Safety Data sheet Replaces Revision 2

Sources of key data used to compile the datasheet

CHIP 2002 EH40

Raw material suppliers Safety Data Sheets.